



Pro-Mix Accelerated Concrete Mix

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.
Issue date: 11/27/2018 Revision date: 6/10/2024 Supersedes: 11/27/2018 Version: 2.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : Pro-Mix Accelerated Concrete Mix

1.2. Recommended use and restrictions on use

Recommended use : Various

1.3. Supplier

Manufacturer

Sakrete of North America
625 Griffith Rd., Ste 100
Charlotte, NC 28217 - USA
T 866-725-7383

1.4. Emergency telephone number

Emergency number : CHEMTREC (800) 424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin Irrit. 2	Causes skin irritation
Eye Dam. 1	Causes serious eye damage
Skin Sens. 1B	May cause an allergic skin reaction
Carc. 1A	May cause cancer
STOT SE 3	May cause respiratory irritation
STOT RE 1	Causes damage to organs (lungs) through prolonged or repeated exposure

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger

Hazard statements (GHS US) : Causes skin irritation
May cause an allergic skin reaction
Causes serious eye damage
May cause respiratory irritation
May cause cancer
Causes damage to organs (lungs) through prolonged or repeated exposure

Precautionary statements (GHS US) : Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash hands, forearms and face thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.

Pro-Mix Accelerated Concrete Mix

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
If exposed or concerned: Get medical advice/attention.
If on skin: Wash with plenty of water.
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center or doctor.
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Quartz	CAS-No.: 14808-60-7	10 - 65
Cement, portland, chemicals	CAS-No.: 65997-15-1	10 - 30
Calcium oxide	CAS-No.: 1305-78-8	5 - 10
Iron oxide (Fe ₂ O ₃)	CAS-No.: 1309-37-1	<5
Aluminum oxide (Al ₂ O ₃)	CAS-No.: 1344-28-1	1 - 5
Sulfuric acid, aluminum salt (3:2)	CAS-No.: 10043-01-3	1 - 5
Sulfuric acid, calcium salt (1:1)	CAS-No.: 7778-18-9	1 - 5
Magnesium oxide (MgO)	CAS-No.: 1309-48-4	0.5 – 1.5
Limestone	CAS-No.: 1317-65-3	0.5 - 1.5

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation : If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact : IF ON SKIN: Wash with plenty of Water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.

Pro-Mix Accelerated Concrete Mix

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.
First-aid measures after ingestion	: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: Dust may cause respiratory tract irritation. Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs.
Symptoms/effects after skin contact	: Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause an allergic skin reaction. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin.
Symptoms/effects after eye contact	: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: May cause cancer through inhalation of dust. Causes damage to organs (lungs) through prolonged or repeated exposure.

4.3. Immediate medical attention and special treatment, if necessary

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: Do not use water jet.

5.2. Specific hazards arising from the chemical

Fire hazard	: Products of combustion may include, and are not limited to: oxides of carbon. Calcium oxide. Aluminum oxides. Iron oxide. Irritating vapors.
-------------	------------------------------------------------------------------------------------------------------------------------------------------------

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).
--------------------------------	--------------------------------------------------------------------------------------------------------------------

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.
------------------	--------------------------------------------------------------------------------------------------------------------------------------

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

Pro-Mix Accelerated Concrete Mix

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

6.3. Methods and material for containment and cleaning up

- For containment : Contain spill, then place in a suitable container. Minimize dust generation. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for cleaning up : Vacuum or sweep material and place in a disposal container. Provide ventilation.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes. Avoid contact with skin and clothing. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Avoid generating dust. Good housekeeping is important to prevent accumulation of dust. The use of compressed air for cleaning clothing, equipment, etc, is not recommended.
- Hygiene measures : Take off contaminated clothing and wash it before reuse. Wash hands, forearms and face thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep out of the reach of children. Store in dust-tight, dry, labelled containers. Keep containers closed when not in use. Avoid any dust buildup by frequent cleaning and suitable construction of the storage area. Do not store in an area equipped with emergency water sprinklers. Store in a dry, cool and well-ventilated place. Store locked up. Keep away from food, drink and animal feedingstuffs.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Pro-Mix Accelerated Concrete Mix	
No additional information available	
Cement, portland, chemicals (65997-15-1)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Portland cement
ACGIH OEL TWA	1 mg/m ³ (particulate matter containing no asbestos and <1% crystalline silica, respirable particulate matter)
Remark (ACGIH)	TLV® Basis: Pulm func; resp symptoms; asthma. Notations: A4 (Not classifiable as a Human Carcinogen)
ACGIH chemical category	Not Classifiable as a Human Carcinogen
Regulatory reference	ACGIH 2020
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)

Pro-Mix Accelerated Concrete Mix

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Cement, portland, chemicals (65997-15-1)	
USA - IDLH - Occupational Exposure Limits	
IDLH	5000 mg/m ³
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA)	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
Sulfuric acid, calcium salt (1:1) (7778-18-9)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	10 mg/m ³ (inhalable particulate matter)
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA)	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
Iron oxide (Fe₂O₃) (1309-37-1)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	5 mg/m ³ (respirable particulate matter)
ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA - OSHA - Occupational Exposure Limits	
Local name	Iron oxide fume
OSHA PEL TWA	10 mg/m ³ (fume) 15 mg/m ³ (total dust (Rouge)) 5 mg/m ³ (respirable fraction (Rouge))
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - IDLH - Occupational Exposure Limits	
IDLH	2500 mg/m ³ (dust and fume)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA)	5 mg/m ³ (dust and fume)
Magnesium oxide (MgO) (1309-48-4)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	10 mg/m ³ (inhalable particulate matter)
ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA	15 mg/m ³ (fume, total particulate)
USA - IDLH - Occupational Exposure Limits	
IDLH	750 mg/m ³ (fume)
Calcium oxide (1305-78-8)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Calcium oxide

Pro-Mix Accelerated Concrete Mix

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Calcium oxide (1305-78-8)	
ACGIH OEL TWA	2 mg/m ³
Remark (ACGIH)	TLV® Basis: URT irr
Regulatory reference	ACGIH 2020
USA - OSHA - Occupational Exposure Limits	
Local name	Calcium oxide
OSHA PEL TWA	5 mg/m ³
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - IDLH - Occupational Exposure Limits	
IDLH	25 mg/m ³
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA)	2 mg/m ³
Aluminum oxide (Al ₂ O ₃) (1344-28-1)	
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
Sulfuric acid, aluminum salt (3:2) (10043-01-3)	
No additional information available	
Limestone (1317-65-3)	
USA - OSHA - Occupational Exposure Limits	
Local name	Calcium Carbonate (Limestone; Marble)
OSHA PEL TWA	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA)	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
Quartz (14808-60-7)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Silica crystalline - quartz
ACGIH OEL TWA	0.025 mg/m ³ (respirable particulate matter)
Remark (ACGIH)	TLV® Basis: Pulm fibrosis; lung cancer. Notations: A2 (Suspected Human Carcinogen)
ACGIH chemical category	Suspected Human Carcinogen
Regulatory reference	ACGIH 2023
USA - OSHA - Occupational Exposure Limits	
Local name	Quartz (Total Dust) (Silica: Crystalline)
OSHA PEL TWA	50 µg/m ³ (Respirable crystalline silica)
Remark (OSHA)	Table Z-3. For OSHA PEL (TWA) use formula: (30 mg/m ³ / (%SiO ₂ +2)) for mg/m ³ . CAS No. source: eCFR Table Z-1.

Pro-Mix Accelerated Concrete Mix

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Quartz (14808-60-7)	
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts
USA - IDLH - Occupational Exposure Limits	
IDLH	50 mg/m ³ (respirable dust)
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL (TWA)	0.05 mg/m ³ (respirable dust)

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.
Environmental exposure controls	: Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:
Wear suitable waterproof gloves
Eye protection:
Wear approved eye (properly fitted dust- or splash-proof chemical safety goggles) / face (face shield) protection.
Skin and body protection:
Wear suitable waterproof protective clothing.
Respiratory protection:
A NIOSH approved dust mask or filtering facepiece is recommended in poorly ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory protection (Z88.2).

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Powder.
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
pH	: 12 – 13
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not flammable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available

Pro-Mix Accelerated Concrete Mix

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

VOC content : 0 % Not applicable; 0 wt, Not applicable.

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions. Keep dry in storage.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Moisture. Incompatible materials.

10.5. Incompatible materials

Wet cement is alkaline and incompatible with acid, ammonium salts and aluminum metal.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. Calcium oxide. Aluminum oxides. Iron oxide. Irritating vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Sulfuric acid, calcium salt (1:1) (7778-18-9)	
LD50 oral rat	> 3000 mg/kg (Source: IUCLID)
LC50 inhalation rat	> 3.26 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
Iron oxide (Fe2O3) (1309-37-1)	
LD50 oral rat	> 10000 mg/kg (Source: IUCLID)
LD50 oral	> 5000 mg/kg body weight Animal: , Guideline: EU Method B.1 (Acute Toxicity (Oral))
Magnesium oxide (MgO) (1309-48-4)	
LD50 oral rat	3870 mg/kg (Source: NLM_HSDB)

Pro-Mix Accelerated Concrete Mix

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Calcium oxide (1305-78-8)	
LD50 oral rat	> 2000 mg/kg body weight Animal: rat, Animal sex: female, Guideline: OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
LD50 dermal rabbit	> 5000 mg/kg body weight Animal: rabbit, Guideline: other:US Federal Register 38: 187, Part 1500, Section 41, 1973.
LC50 inhalation rat	> 6.04 mg/l/4h
Aluminum oxide (Al ₂ O ₃) (1344-28-1)	
LD50 oral rat	> 5000 mg/kg (Source: IUCLID)
Sulfuric acid, aluminum salt (3:2) (10043-01-3)	
LD50 oral rat	1930 mg/kg (Source: NLM_HSDB)
LD50 dermal rabbit	> 1167.5 mg/kg body weight Animal: rabbit, Animal sex: female, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
Skin corrosion/irritation	: Causes skin irritation. pH: 12 – 13
Sulfuric acid, calcium salt (1:1) (7778-18-9)	
pH	6 – 7.6 (conc: 20 % (aqueous solution))
Magnesium oxide (MgO) (1309-48-4)	
pH	10.3 (saturated aqueous solution)
Calcium oxide (1305-78-8)	
pH	12.5 (saturated solution)
Sulfuric acid, aluminum salt (3:2) (10043-01-3)	
pH	2.9 (conc: 1000 g/L (water))
Serious eye damage/irritation	: Causes serious eye damage. pH: 12 – 13
Sulfuric acid, calcium salt (1:1) (7778-18-9)	
pH	6 – 7.6 (conc: 20 % (aqueous solution))
Magnesium oxide (MgO) (1309-48-4)	
pH	10.3 (saturated aqueous solution)
Calcium oxide (1305-78-8)	
pH	12.5 (saturated solution)
Sulfuric acid, aluminum salt (3:2) (10043-01-3)	
pH	2.9 (conc: 1000 g/L (water))
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer.
Sulfuric acid, calcium salt (1:1) (7778-18-9)	
NOAEL (chronic,oral,animal/male,2 years)	256 mg/kg body weight Animal: rat, Animal sex: male, Guideline: other:No data, Remarks on results: other:Effect type: carcinogenicity (migrated information)

Pro-Mix Accelerated Concrete Mix

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Sulfuric acid, calcium salt (1:1) (7778-18-9)	
NOAEL (chronic,oral,animal/female,2 years)	284 mg/kg body weight Animal: rat, Animal sex: female, Guideline: other:No data, Remarks on results: other:Effect type: carcinogenicity (migrated information)
Iron oxide (Fe2O3) (1309-37-1)	
IARC group	3 - Not classifiable
Quartz (14808-60-7)	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	Known Human Carcinogens
In OSHA Hazard Communication Carcinogen list	Yes
Reproductive toxicity	: Not classified
Aluminum oxide (Al2O3) (1344-28-1)	
NOAEL (animal/male, F0/P)	1000 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Sulfuric acid, aluminum salt (3:2) (10043-01-3)	
LOAEL (animal/male, F0/P)	27.371 mg/kg body weight Animal: other:rat and mouse, Animal sex: male, Guideline: EPA OTS 798.4700 (Reproduction and Fertility Effects), Remarks on results: other:Generation: Effects on spermatogenesis, testis, epididymis, in the ductus deferens, interstitium (migrated information)
NOAEL (animal/female, F0/P)	310 mg/kg body weight Animal: mouse, Animal sex: female, Guideline: EU Method B.35 (Two-Generation Reproduction Toxicity Test), Remarks on results: other:Generation: F3 (migrated information)
NOAEL (animal/female, F1)	310 mg/kg body weight Animal: mouse, Animal sex: female, Guideline: EU Method B.35 (Two-Generation Reproduction Toxicity Test)
STOT-single exposure	: May cause respiratory irritation.
Cement, portland, chemicals (65997-15-1)	
STOT-single exposure	May cause respiratory irritation.
Calcium oxide (1305-78-8)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Causes damage to organs (lungs) through prolonged or repeated exposure. Respirable crystalline silica in the form of quartz or cristobalite from occupational sources is listed by the International Agency for Research on Cancer (IARC) and National Toxicology Program (NTP) as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to the amount of dust exposure and the length of time (usually years) of exposure.
Sulfuric acid, calcium salt (1:1) (7778-18-9)	
LOAEL (oral, rat, 90 days)	237 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (oral, rat, 90 days)	79 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Pro-Mix Accelerated Concrete Mix

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Iron oxide (Fe₂O₃) (1309-37-1)	
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.2102 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	≥ 0.03 mg/l air Animal: rat, Animal sex: male
Calcium oxide (1305-78-8)	
LOAEL (oral, rat, 90 days)	300 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEL (oral, rat, 90 days)	1000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.413 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study)
Aluminum oxide (Al₂O₃) (1344-28-1)	
LOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.015 mg/l air Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.07 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
Quartz (14808-60-7)	
STOT-repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Sulfuric acid, aluminum salt (3:2) (10043-01-3)	
Viscosity, kinematic	6.273 mm ² /s
Symptoms/effects after inhalation	: Dust may cause respiratory tract irritation. Respirable crystalline silica (quartz) can cause silicosis, a fibrosis (scarring) of the lungs.
Symptoms/effects after skin contact	: Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. May cause an allergic skin reaction. May cause burns in the presence of moisture. Skin contact during hydration may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow continuous, prolonged contact with skin. Handling can cause dry skin.
Symptoms/effects after eye contact	: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: May cause cancer through inhalation of dust. Causes damage to organs (lungs) through prolonged or repeated exposure.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No ecological consideration when used according to directions.

Sulfuric acid, calcium salt (1:1) (7778-18-9)	
LC50 - Fish [1]	2980 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static] Source: EPA)
LC50 - Fish [2]	> 1970 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)
EC50 72h - Algae [1]	> 79 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

Pro-Mix Accelerated Concrete Mix

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Iron oxide (Fe ₂ O ₃) (1309-37-1)	
LC50 - Fish [1]	100000 mg/l (Exposure time: 96 h - Species: Danio rerio [static] Source: ECHA)
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
EC50 - Other aquatic organisms [1]	> 100 mg/l Test organisms (species):
EC50 72h - Algae [1]	> 20 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

Calcium oxide (1305-78-8)	
LC50 - Fish [1]	1070 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [static] Source: IUCLID)
EC50 - Crustacea [1]	49.1 mg/l Test organisms (species): Daphnia magna
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	1130.3 mg/l Test organisms (species): Navicula seminulum
NOEC (chronic)	32 mg/l Test organisms (species): Crangon septemspinosa Duration: '14 d'
NOEC chronic fish	100 mg/l Test organisms (species): other:Tilapia nilotica Duration: '46 d'

Aluminum oxide (Al ₂ O ₃) (1344-28-1)	
EC50 72h - Algae [1]	1.05 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	0.2 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

Sulfuric acid, aluminum salt (3:2) (10043-01-3)	
LC50 - Fish [1]	27.9 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: ECHA)
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna
LC50 - Fish [2]	228.5 mg/l Test organisms (species): Pimephales promelas
EC50 72h - Algae [1]	> 100 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
LOEC (chronic)	27 mg/l Test organisms (species): Daphnia magna Duration: '28 d'
NOEC (chronic)	12 mg/l Test organisms (species): Daphnia magna Duration: '28 d'

12.2. Persistence and degradability

Pro-Mix Accelerated Concrete Mix	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Pro-Mix Accelerated Concrete Mix	
Bioaccumulative potential	Not established.

Calcium oxide (1305-78-8)	
BCF - Fish [1]	(no bioaccumulation)

Sulfuric acid, aluminum salt (3:2) (10043-01-3)	
BCF - Fish [1]	76 – 190 (organ w.w.)

Pro-Mix Accelerated Concrete Mix

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other information : No other effects known.

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. The generation of waste should be avoided or minimized wherever possible.

SECTION 14: Transport information

In accordance with DOT

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not applicable

14.3. Transport hazard class(es)

DOT
Transport hazard class(es) (DOT) : Not applicable

14.4. Packing group

Packing group (DOT) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

15.2. International regulations

No additional information available

Pro-Mix Accelerated Concrete Mix

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

15.3. US State regulations



WARNING:

This product can expose you to crystalline silica, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Issue date : 11/27/2018
Revision date : 06/10/2024
Other information : None.
Prepared by : Nexreg Compliance Inc.
www.Nexreg.com



Full text of H-phrases	
Carc. 1A	Carcinogenicity Category 1A
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1B	Skin sensitization, category 1B
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

Indication of changes:
SDS update.

Safety Data Sheet (SDS), USA

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.